

Zhejiang GS Forklift Truck Co., Ltd.

E-mail: sales@forklift-manufacturers.com URL: http://www.forklift-manufacturers.com/

Technical Parameter:

		Model		FB10-C1	FB15-C1	
Specification	1	Model				
	2	Rated Capacity		kg	1000	1500
	3	Load Centre		mm	500	500
	4	Lifting Height		mm	3000	3000
	5	Fork Size	LxWxT	mm	920x100x35	920x100x35
	6	Tilting Angle	F/R (α°/β°)	Deg	6/12	6/12
Dimensions	7	Overall Dimension	Length (to fork face)	mm	2020	2020
	8		Overall Width	mm	1070	1070
	9		Height When Mast Lowered	mm	1985	1985
	10		Height When Mast Lifting	mm	4030	4030
	11		Safeguard Height	mm	2050	2050
	12	Turning Radius	Min.	mm	1800	1800
	13	Front Overhang		mm	420	420
	14	Tread	(Front/Rear)	mm	890/920	890/920
	15	Ground Clearance	Min.	mm	100	100
	16	Wheelbase		mm	1250	1250
	17	Fork Spread	Min./Max.	mm	200/1000	200/1000
Performance	18	Speed	Travel (Laden)	km/h	13	13
	19		Lifting (Laden)	mm/s	300	270
	20	Gradeability	Laden	%	15	15
	21	Service Weight (include battery)		kg	2890	2990
	22	Tire	Frontx2		6.50-10-10PR	6.50-10-10PR
	23		Rearx2		5.00-8-8PR	5.00-8-8PR
Driven	24	Motor	Driven Motor	kw	5	5
	25		Lift Motor	kw	7.5	7.5
	26	Battery	Standard	V/Ah	48/400	48/400
	27	Controller	Manufacturer		CURTIS	CURTIS
	28	Operating Pressure for Attachment		Mpa	14.5	14.5