

Zhejiang GS Forklift Truck Co., Ltd.

E-mail: sales@forklift-manufacturers.com URL: <http://www.forklift-manufacturers.com/>

Technical Parameter:

Specification	1	Model		FB20-C1	FB25-C1
		2	Rated Capacity	kg	2000
	3	Load Centre	mm	500	500
	4	Lifting Height	mm	3000	3000
	5	Fork Size	LxWxT	1070x122x40	1070x122x40
	6	Tilting Angle	F/R (α°/β°)	6/12	6/12
Dimensions	7	Overall Dimension	Length (to fork face)	mm	2365
	8		Overall Width	mm	1150
	9		Height When Mast Lowered	mm	1995
	10		Height When Mast Lifting	mm	4030
	11		Safeguard Height	mm	2095
	12	Turning Radius	Min.	mm	1945
	13	Front Overhang		mm	482
	14	Tread	(Front/Rear)	mm	960/950
	15	Ground Clearance	Min.	mm	120
	16	Wheelbase		mm	1450
	17	Fork Spread	Min./Max.	mm	245/1100
Performance	18	Speed	Travel (Laden)	km/h	13
	19		Lifting (Laden)	mm/s	240
	20	Gradeability	Laden	%	11
	21	Service Weight (include battery)		kg	3800
	22	Tire	Frontx2		7.00-12-12PR
	23		Rearx2		18x7-8-14PR
Driven	24	Motor	Driven Motor	kw	7.5
	25		Lift Motor	kw	8.5
	26	Battery	Standard	V/Ah	48/630
	27	Controller	Manufacturer		CURTIS
	28	Operating Pressure for Attachment		Mpa	17.5