

Zhejiang GS Forklift Truck Co., Ltd.

E-mail: sales@forklift-manufacturers.com URL: <http://www.forklift-manufacturers.com/>

Technical Parameter:

Specification	1	Model			FB20-Z1	FB25-Z1
	2	Rated Capacity		kg	2000	2500
	3	Load Centre		mm	500	500
	4	Lifting Height		mm	3000	3000
	5	Fork Size	LxWxT	mm	1070x122x40	1070x122x40
	6	Tilting Angle	F/R (α°/β°)	Deg	6/12	6/12
Dimensions	7	Overall Dimension	Length (to fork face)	mm	2365	2365
	8		Overall Width	mm	1150	1150
	9		Height When Mast Lowered	mm	1995	1995
	10		Height When Mast Lifting	mm	4030	4030
	11		Safeguard Height	mm	2095	2095
	12	Turning Radius	Min.	mm	1945	1945
	13	Front Overhang		mm	482	482
	14	Tread	(Front/Rear)	mm	960/950	960/950
	15	Ground Clearance	Min.	mm	120	120
	16	Wheelbase		mm	1450	1450
17	Fork Spread	Min./Max.	mm	245/1100	245/1100	
Performance	18	Speed	Travel (Laden)	km/h	13	13
	19		Lifting (Laden)	mm/s	240	225
	20	Gradeability	Laden	%	11	11
	21	Service Weight (include battery)		kg	3800	4100
	22	Tire	Frontx2		7.00-12-12PR	7.00-12-12PR
	23		Rearx2		18x7-8-14PR	18x7-8-14PR
Driven	24	Motor	Driven Motor	kw	7.5	7.5
	25		Lift Motor	kw	8.5	8.5
	26	Battery	Standard	V/Ah	48/630	48/630
	27	Controller	Manufacturer		ZAPI	ZAPI
	28	Operating Pressure for Attachment		Mpa	17.5	17.5